

(12) UK Patent Application (19) GB (11) 2 367 530 (13) A

(43) Date of A Publication 10.04.2002

(21) Application No 0024204.0

(22) Date of Filing 03.10.2000

(71) Applicant(s)
Nokia Mobile Phones Limited
(Incorporated in Finland)
Keilalahdentie 4, 02160 Espoo, Finland

(72) Inventor(s)
Andrew Raymond Bick

(74) Agent and/or Address for Service
Venner Shipley & Co
20 Little Britain, LONDON, EC1A 7DH,
United Kingdom

(51) INT CL⁷
G06F 3/02

(52) UK CL (Edition T)
B6F FCHK

(56) Documents Cited
None

(58) Field of Search
UK CL (Edition S) **B6F FCHK**
INT CL⁷ **G06F 3/023 , G06K 11/18 , H04M 1/02 1/23**
ONLINE DATABASES: EPODOC, JAPIO, WPI

(54) Abstract Title
User interface device

(57) A keypad (7) of a mobile telephone handset comprises a keymat (17) beneath which are disposed capacitive sensing plates (20, 21). The keypad may be used in a conventional manner to enter alphanumeric data by pressing keys (18) or as a touch pad by sliding a finger over the surface of the keymat (17).




Figure 3

GB 2 367 530 A




Figure 1




Figure 2




Figure 3




Figure 4




Figure 5




Figure 6

User Interface Device

Description

The present invention relates to a user interface device particularly but not
5 exclusively for a mobile telephone handset or digital communicator handset.

Portable electronic apparatus are increasingly able to support powerful software applications requiring sophisticated user interfaces. For example, laptop computers, mobile telephone handsets, personal digital assistants (PDAs) and digital
10 communicator handsets can run browser software which enables a user to navigate content on a web page by selecting hypertext links.

Conventional mobile telephone handsets have an alphanumeric keypad comprising a set of dual-state keys arranged in a grid pattern. Although the keypad is appropriate
15 for entering text and numbers, it is not particularly suited to navigating a web page because movement of a pointer or cursor is restricted to discrete steps and is constrained to orthogonal directions defined by the grid pattern.

The present invention seeks to provide an improved user interface.
20

According to the present invention, there is provided a user interface device for electronic apparatus, the device comprising a keypad having a plurality of keys each arranged to actuate a respective switch so as to provide a first type of user input and integrally disposed impedance sensing means so as to provide a second type of user
25 input.

The keypad may include a region provided with said impedance sensing means but without a key. The keys may be comprised in a keymat and the impedance sensing means may be disposed beneath the keymat. The keymat and the impedance sensing means may be coextensive. The keys may comprise silicone rubber and may
30 include a hard coat.

The impedance sensing means may be arranged to detect the presence of a digit and may comprise first and second sensing plates.

5 The first sensing plate may comprise a first set of electrodes, arranged in non-contiguous stripes. The electrodes may be transparent and made from indium-tin-oxide. The first sensing plate may comprise a substrate, which is transparent and made from polyethylene terephthalate.

10 The second sensing plate may comprise a second set of electrodes. The first and second set of electrodes are spaced apart. A first member of the first set of electrodes and a first member of the second set of electrodes may be arranged to have a mutual capacitance and configured so to allow the mutual impedance to change when a digit touches the keypad.

The impedance sensing means may be a capacitive sensing means.

The device may further comprise a light source to illuminate the keypad, disposed behind the keys and may be planar. The light source is an electroluminescent layer.

15 The first type of user input may be input of alphanumeric data and the second type of user input may be control of a focus on a display of the electronic apparatus.

20 According to the present invention there is also provided an electronic apparatus incorporating a user interface device comprising a keypad having a plurality of keys each arranged to actuate a respective switch so as to provide a first type of user input and integrally disposed impedance sensing means so as to provide a second type of user input.

The electronic apparatus may be portable and may be a mobile telephone, communicator handset or personal computer.

25 According to the present invention there is also provided a method of fabricating a user interface device for electronic apparatus, the method comprising providing a keypad having a plurality of keys each arranged to actuate a respective switch so as

to provide a first type of user input and integrally disposing impedance sensing means so as to provide a second type of user input.

5 An embodiment of the present invention will now be described by way of example with reference to the accompanying drawings, in which:

Figure 1 is a perspective view of a mobile telephone handset;

Figure 2 is a schematic diagram of mobile telephone circuitry;

Figure 3 is an exploded perspective view of an embodiment of the present
10 invention;

Figure 4 is cross-sectional view taken along the line A-A' as shown in Figure 3;

Figure 5 is a plan view of the embodiment shown in Figure 3 and

Figure 6 shows a pointer displayed on a screen of the mobile telephone handset.

15 Referring to Figures 1 and 2, a mobile telephone handset 1 comprises a case 2, a battery 3, a liquid crystal display (LCD) panel 4, a microphone 5, ear piece 6, a keypad 7 having a key interface 8 and a capacitive sensing means interface 9, an antenna 10, subscriber identification module (SIM) card 11 and SIM card reader 12. The mobile telephone circuitry includes radio interface circuitry 13, codec circuitry
20 14, controller 15 and memory 16. Individual circuits and elements are of a type well-known in the art, for example a Nokia range in mobile telephones.

Referring to Figures 1, 3, 4 and 5, cutaway portions 7', 2' of the keypad 7 and case 2 are shown. The keypad 7 comprises a silicone rubber keymat 17 having a plurality
25 of keys 18. Letters and numerals are laser-etched into the surface of the keys 18 and the keys 18 are provided with a hard protective coat (not shown). A capacitive sensing means 19 lies beneath the keymat 17 and comprises first and second sensing plates 20, 21. The first sensing plate 20 comprises a first set of striped indium-tin-oxide (ITO) electrodes 22 mounted on a first polyethylene terephthalate (PET)
30 substrate 23. Similarly, the second sensing plate 21 comprises a second set of striped ITO electrodes 24 mounted on a second PET substrate 25. The first and second sets of electrodes 22, 24 run in orthogonal directions. For example, the first set of electrodes 22 are arranged to run parallel to the x-axis, while the second set of

electrodes 24 run parallel to the y-axis. The first and second sensing plates 20, 21 are bonded together by means of a first optical adhesive layer 26. A second optical adhesive layer 27 is used to bond the sensing means 19 to the keymat 17. A third optical adhesive layer 28 is used to bond an electroluminescent back light layer 29 to the underside of the sensing means 19. When powered, the electroluminescent layer 29 illuminates the letters and numerals etched into the keys 18. The electroluminescent layer 29 is mounted to a dome adhesive gasket 30 which is adhered to a flexible substrate 31 on which metal dome switches 32 are mounted. Each dome 32 lies beneath a respective key 18, for example as shown in Figures 4 and 5. First and second metal contacts 33a, 33b are mounted on the substrate 31 beneath each dome 32. The second contact 33b is concentric with the first contact 33a. Each dome 32 sits upon a respective second metal contact 33b having the greater radius of the two contacts 33a, 33b. Respective nodules 34 on the underside of the dome adhesive gasket are used to help increase the so-called "snap ratio force" of the domes 32 when force is applied to the keys 18. Thus, this provides better tactile feel when the keys 18 are pressed.

The keypad 7 may operate as a conventional keypad and, either independently or simultaneously, as a touch sensitive pointing device.

As a conventional keypad, a user depresses a "hash" key 18a and force is transmitted through underlying layers 20, 21, 26, 27, 28, 29, 30 to deform a first key dome 32a lying underneath. Deformation of the first key dome 32a completes electrical connection between the first and second contacts 33a, 33b. This causes a signal to be generated and processed by the key interface 8 and the controller 15 in a well-known manner. This may result in the screen 4 displaying a "#" symbol. In this example, the key interface 8 generates signals which are passed to the controller 15 which runs suitable keypad driver software.

As a touch-sensitive pointing device, a user lightly touches the keymat 17 without exerting enough force to depress any of the keys 18. Beneath the user's finger lies an intersection 35 of a first electrode 22a of the first sensing plate 20 and a second electrode 24a of the second sensing plate 21. The user's finger modifies the mutual

capacitance between the first and second electrodes 22a, 24a, which is detected by sensing means interface 9 in a well-known manner so as to determine the co-ordinate of the user's finger, which is fed to the controller 15. The controller runs suitable touchpad driver software. The user slides their finger over the surface of the keymat 17 and uses it as if it were a conventional touch pad. This is particularly
5 useful when navigating a cursor 36 around a web page 37 displayed on the display 4 in order to select a hypertext link 38 as shown in Figure 6. Hypertext link 38 may be selected by lightly double tapping on the surface of the keymat 17. In this example, the whole area of the keymat 17 serves as a touch pad and not simply the
10 keys 18. There are regions of the keymat 17, for example between the keys 18, where the user is not able to press a key but is able to control the cursor using capacitive sensing means pointing device. It will be appreciated that the user need not touch the keypad 7 to change the mutual capacitance between the electrodes. For example, the change in mutual capacitance may be sufficient enough to be
15 detected if the user holds their finger less than a millimetre above the surface of the keypad 7.

It will be appreciated that many modifications may be made to the embodiment hereinbefore described. For example, a resistive sensing means, such as those used
20 in resistive touch sensitive screens, may be used instead of a capacitive sensing means. The sensing means substrate may be made from other suitable plastics materials such as acrylic or polythene. The electrodes may be made from other conductive materials such as conductive polymers or thin metallic films. The keys need not be proud of the keypad. The keypad may be integrated into the case of
25 the handset. A portion of the area of the keymat may serve as a touch pad.

It will be appreciated that the invention can be used in relation to any sort of electronic apparatus, be it portable and non-portable. This may include mobile telephone handsets and laptop computers. It may also be used in a remote control
30 unit for electronic apparatus such as television sets, multimedia set-top boxes and audio equipment.

Claims

1. A user interface device for electronic apparatus, the device comprising a keypad having a plurality of keys each arranged to actuate a respective switch so as
5 to provide a first type of user input and integrally disposed impedance sensing means so as to provide a second type of user input.
2. A device according to claim 1, wherein the keypad includes a region provided with said impedance sensing means but without a key.
3. A device according to claim any preceding claim, wherein said keys are
10 comprised in a keymat.
4. A device according to claim 3, wherein the impedance sensing means is disposed adjacently to the keymat.
5. A device according to claim 3 or 4, wherein the keymat and the impedance sensing means are coextensive.
- 15 6. A device according to any preceding claim, wherein the keys comprise silicone rubber.
7. A device according to any preceding claim, wherein the keys include a hard coat.
8. A device according to any preceding claim, wherein the impedance sensing
20 means is arranged to detect the presence of a digit.
9. A device according to any preceding claim, wherein the impedance sensing means comprises first and second sensing plates.
10. A device according to claim 9, wherein the first sensing plate comprises a first set of electrodes.

11. A device according to claim 10, wherein the electrodes are arranged in non-contiguous stripes.
12. A device according to claim 10 or 11, wherein the electrodes are transparent.
13. A device according to claim 10, 11 or 12, wherein the electrodes are made
5 from indium-tin-oxide.
14. A device according to any one of claims 9 to 13, wherein the first sensing plate comprises a substrate.
15. A device according to claim 14, wherein the substrate is substantially transparent.
- 10 16. A device according to claim 14 or 15, wherein the substrate is made from polyethylene terephthalate.
17. A device according to any one of claims 10 to 16, wherein the second sensing plate comprises a second set of electrodes.
18. A device according to claim 17, wherein the first and second set of
15 electrodes are spaced apart.
19. A device according to claim 18, wherein a first member of the first set of electrodes and a first member of the second set of electrodes are arranged to have a mutual capacitance.
20. A device according to claim 19, wherein said members are arranged so to
20 allow the mutual capacitance to change when a digit touches the keypad.
21. A device according to any preceding claim, wherein the impedance sensing means is a capacitive sensing means.

22. A device according to any preceding claim, further comprising a light source to illuminate the keypad.
23. A device according to claim 22, wherein the light source is disposed behind the keys.
- 5 24. A device according to claim 22 or 23, wherein the light source is planar.
25. A device according to any one of claims 22 to 24, wherein the light source is an electroluminescent layer.
26. A device according to any preceding claim wherein the first type of user input is input of alphanumeric data.
- 10 27. A device according to any preceding claim wherein the second type of user input is control of a focus on a display of the electronic apparatus.
28. A user interface device substantially as hereinbefore described with reference to Figures 3, 4 and 5 of the accompanying drawings.
29. Electronic apparatus incorporating a device according to any preceding
15 claim.
30. Electronic apparatus according to claim 29, which is portable.
31. A mobile telephone handset incorporating a device according to any one of claims 1 to 28.
32. An electronic communicator handset incorporating a device according to any
20 one of claims 1 to 28.
33. A portable computer incorporating a device according to any one of claims 1 to 28.

34. A method of fabricating a user interface device for electronic apparatus comprising providing a keypad having a plurality of keys each arranged to actuate a respective switch so as to provide a first type of user input and integrally disposing impednace sensing means so as to provide a second type of user input.



Application No: GB 0024204.0
Claims searched: 1-34

Examiner: A J Rudge
Date of search: 27 February 2001

Patents Act 1977 Search Report under Section 17

Databases searched:

UK Patent Office collections, including GB, EP, WO & US patent specifications, in:

UK CI (Ed.S): B6F(FCHK)

Int CI (Ed.7): G06F-3/023;G06K-11/18;H04M-1/02;1/23

Other: Online databases: EPODOC, JAPIO, WPI

Documents considered to be relevant:

Category	Identity of document and relevant passage	Relevant to claims
	None	

N	Document indicating lack of novelty or inventive step	A	Document indicating technological background and/or state of the art.
Y	Document indicating lack of inventive step if combined with one or more other documents of same category.	P	Document published on or after the declared priority date but before the filing date of this invention.
&	Member of the same patent family	E	Patent document published on or after, but with priority date earlier than, the filing date of this application.